

**Brass Standoffs Male Standoffs Brass Male Hex stand off pillars Brass Pillars**

**Brass Standoffs Male Standoffs Brass Male Hex stand off pillars Brass Pillars**



**Brass Standoffs Male Standoffs  
Brass Male Hex stand off pillars  
Brass Pillars**

Brass Stand-off pillar Thread	Thread Stud Length (X)	Hole Depth (Y)
M3	8.0 - 10.0	3.0 - 10.0
M4	8.0 - 10.0	2.5 - 10.0
M5	8.0 - 10.0	2.5 - 10.0
M6	12.0	6.0 - 13.0
M8	14.0	8.0 - 15.0

Thread	A/F	Lengths Available
M3	5.0	5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M4	7.0	5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M5	8.0	5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M6	10.0	10, 12, 15, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80

M8	13.0	15, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100
----	------	---

**We manufacture a wide range of Brass male standoffs  
Female stand-off Pillars Brass pillars male /female pillars  
with Nickel and Tin plating.**

We have a wide range of Brass stand offs and Brass spacers designed for use in printed Circuit Board. These standoffs are available in Round & Hex shapes.	
Standoff Sizes & Types	Brass spacers and Standoffs are produced with metric , American UNC or UNF threads. But we also produce the same in Metric (mm) threads & Withworth Threads. Round & Hex shapes in Spacer as well as in Standoffs are available. M3, M4, M5 & 4-40 UNC are our standard series of Spacers & Standoffs. Also Jack Screw Type standoff (Female Screw Lock) is having special concern in our standard range of series. And any custom design part can be manufactured on demand.
Standoff Threads	UNC 2-56, 4-40, 6- 32, 8-32, 10-32 UNC, UNEF, UNF, ISO Metric (MM Threads) BA, BSW (Inches), UNC, UNF or Any as per custom design.
Material	Free machining Brass CDA 360 ROHS complaint. c345, C 353, CDA 36000, c3602, c3604, c385, cz131,cz124, cz121, en 12164 - cw606n, CW 603n,CW 614n, cuzn36pb2, cuzn39pb3 & cuzn36pb3. - c377, c380, cz122, en 12165 - cw617n, cw612n, cuzn40pb2 & cuzn39pb2. C 675, cz 114, cz 115, en 12165 CW 721 r & CW 722r. c3533, cz132, cw602n & cuzn36pb2as. They Can also be manufactured in Stainless Steel 304, Stainless Steel 316 grade. custom specification Any Special Brass Material Composition as per customers requirement
Applications	A standoff is used in mechanics and electronics to separate two parts from one another. Standoffs can be many shapes and sizes and made of many different materials. Insulating standoffs keeps two parts from touching each other, thereby preventing an electronic short. Cable thumbscrews are often screwed into standoffs on the back of computers.
Finish & Coating	Brass Stand-ooFs and Brass pillars (hex and round) are offered in Natural, Nickle Plated, chrome plated, Tin Plated available for brass male female pillars, brass stand off, brass spacer and brass distance bolts or any coating as per customer specification. Any kind of brass male female pillars, brass stand off, brass spacer and brass distance bolts can be developed and supplied exactly as per customer specifications.

**ADDEESS:**  
**BRASS NEUTRAL LINKS PRIVATE LIMITED**

**CONTACTS:**  
PHONE : 91-22-43449300/27

Plot 12  
GIDC Ind estate  
Udyognagar  
Jamnagar 361005 Gujarat  
India

FAX : 91-22-22834046  
EMAIL : [info@brass-neutral-links.com](mailto:info@brass-neutral-links.com)  
**[CONTACT US](#) | [BACK TO HOME PAGE](#)**

**KEYWORDS:**